

DATASHEET

Wall Cabinet X-Rack w. glass door 400-600mm 9U Black RAL9005



General data

Steel sheet housing with swiveling frame, self-ventilated, not pre-assembled
 Housing continuously depth adjustable from 400 .. 600 mm
 Secured side walls, can only be removed after opening front door
 Inside front-sided 2 x 19" profile, additionally depth-adjustable by 50 mm
 Front door with window of certified safety-glass (4 mm) and latch locking
 Door stop changeable due to stable, spring-loaded metal hinges
 Door angle adjustable due to adjustable hinges
 Door opening angle 120°
 Roof and bottom with pre-punched openings for cable entry (190 x 90 mm)
 Rear sided open frame with additionally positions for cable management
 Roof and bottom prepared for accommodation of single fan Art.-No. 691664

This datasheet was created automatically on 27-02-2026 . Technical changes reserved.



DATASHEET

Wall Cabinet X-Rack w. glass door 400-600mm 9U Black RAL9005

Cabinet parts inside completely grounded, M5 grounding bolt at base frame

Max. load 60 kg (statically equally distributed), protection degree IP20

Paint finish RAL7035, light grey / RAL9005, jet black

Scope of delivery: 2 x key, earthing cable

Delivery un-assembled in transport packaging (3 packages, rear frame + outer parts + front door)

Technical properties

Cabinet Series	19" Wall Housing X-Rack, un-assembled
Cable entry roof/floor	Roof+ base, each 190 x 90 mm, open back
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Door opening angle front door	> 180 °
Frame	Locking mechanism
Installation depth min. - max.	310 - 510 mm
Material	Steel
Model	With permanent frame
Modular spacing	482.6 mm (19 inch)
Mounting level	Front side
Number of cartons	3
Number of doors	1
Packaging	3 cartons, strapped
Scope of delivery	1x Cabinet
Structure/Use	19" wall-mounted enclosure, depth adjustable to 400/450/500/550/600mm.
Surface finishing	powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

This datasheet was created automatically on 27-02-2026 . Technical changes reserved.



DATASHEET

Wall Cabinet X-Rack w. glass door 400-600mm 9U Black RAL9005

ArtNr.	Bezeichnung	Color	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGX-0906GR.G1	Wall Cabinet X-Rack w. glass door 400-600mm 9U Grey RAL7035	grey	400-600 mm	500 mm	60 kg	9 U	600 mm	7035
WGX-0906TS.G1	Wall Cabinet X-Rack w. glass door 400-600mm 9U Black RAL9005	black	400-600 mm	500 mm	60 kg	9 U	600 mm	9005
WGX-1206GR.G1	Wall Cabinet X-Rack w. glass door 400-600mm 12U Grey RAL7035	grey	400-600 mm	600 mm	60 kg	12 U	600 mm	7035
WGX-1206TS.G1	Wall Cabinet X-Rack w. glass door 400-600mm 12U Black RAL9005	black	400-600 mm	600 mm	60 kg	12 U	600 mm	9005
WGX-1506GR.G1	Wall Cabinet X-Rack w. glass door 400-600mm 15U Grey RAL7035	grey	400-600 mm	766 mm	60 kg	15 U	600 mm	7035
WGX-1506TS.G1	Wall Cabinet X-Rack w. glass door 400-600mm 15U Black RAL9005	black	400-600 mm	766 mm	60 kg	15 U	600 mm	9005

This datasheet was created automatically on 27-02-2026 . Technical changes reserved.

