



24-Port 10/100/1000 Base-T +2x



Tuote

Tuotekoodi: GS-4210-24P2S

Tekniset tiedot





Physical Port

- 24-port 10/100/1000BASE-T Gigabit RJ45 copper
- 2 100/1000BASE-X mini-GBIC/SFP slots

24-Port 10/100/1000 Base-T +2x

RJ45 copper interface for switch basic management and setup

- Reset button for system factory default and reboot

Switching

- Hardware-based 10/100Mbps, half/full duplex and 1000Mbps full duplex mode, flow control and auto-negotiation, and auto MDI/MDI-X

- Features Store-and-Forward mode with wire-speed filtering and forwarding rates

- IEEE 802.3x flow control for full duplex operation and back pressure for half duplex operation

- 9K jumbo frame

- Automatic address learning and address aging

- Supports CSMA/CD protocol
- Power over Ethernet

- Complies with IEEE 802.3at High Power over Ethernet

- Complies with IEEE 802.3af Power over Ethernet

- Up to 24 ports of IEEE 802.3af/802.3at devices powered

- Supports PoE Power up to 30.8 watts for each PoE port

- 300-watt PoE budget

- Auto detects powered device (PD)

- Circuit protection prevents power interference between ports

- Remote power feeding up to 100 meters in standard mode and 250m in extend mode

- PoE Management
 - Total PoE power budget control
 - Per port PoE function enable/disable
 - PoE Port Power feeding priority
 - Per PoE port power limitation
 - PoE delay
 - PD classification detection

- Intelligent PoE features
 - PoE usage threshold control
 - PD alive check
 - PoE schedule

Layer 2 Features

- Prevents packet loss with back pressure (half-duplex) and IEEE 802.3x pause frame flow control (full-duplex)

- High performance Store and Forward architecture, runt/CRC filtering eliminates erroneous packets to optimize the network bandwidth

- Supports VLAN
 - IEEE 802.1Q tagged VLAN
 - Provider Bridging (VLAN Q-in-Q) support (IEEE 802.1ad)