19" PDU strip with 6xSCHUKO



Tuote

Tuotekoodi: MXL048S062

Tekniset tiedot

SERVER RACK PDU - 1 PHASE 1x16A
MXL047S062
6 x Schuko sockets outlet (German standard) max. 16A/230VAC
Schuko sockets 45° oriented
Plastic elements colour: light-grey similar to RAL7035
Natural anodized aluminium body
Dimensions without mounting brackets (WxHxD): 431x44x44mm
Vertical or horizontal mounting in 19" rack - 1U
Mounting brackets for installation in 4 orientations
2-meter supply cable H05VV-F.3G1,5mm² in white or black colour.
Supply cable terminated unischuko angled plug 16A/230V.
Maximum current 16A (3680 W).
Surge arrester - protection against overvoltage

- energy absorption: 400J (L/N), 200J (L,N/PE) - 10/1000µs.

- nominal peak current: 7 kA (8/20µs).

- maximal peak current: 10 kA (udar 8/20µs).

- applied voltage: 480V (L/N), 840V (L,N/PE).

- protection voltage level: 790V (L/N), 1540V (L,N/PE).

- response time: < 25ns.
RFI noise filter.

symmetric mode asymmetric mode

f(MHz) 0,15 1 4,7 10 30 f(MHz) 0,15 1 4,7 10 30

A(dB) 29 42 30 47 43 A(dB) 25 62 64 43 22
Protection level IP20.
Declaration of Conformity CE.