MONITORED POWER DISTRIBUTION



Tuote

Tuotekoodi: MXLR5VV933-05331

Tekniset tiedot

MONITORED POWER DISTRIBUTION UNIT
catalogue number: MXLR5VV933-05331
9 x IEC320C13 sockets outlet max. 10A/230VAC
3 x IEC320C19 sockets outlet max. 16A/230VAC
Sockets are located in 3 blocks. Each block is protected by circuit breaker for overload and short circuit. MCB tripping characteristic - type C, 16A, 2-pole.
Plastic elements colour: light-grey similar to RAL7035
Natural anodized aluminium body.
Dimensions without mounting brackets (WxHxD): 44x1076x90mm
Vertical mounting in 19" rack - 0U
Mounting brackets for installation in 4 orientations
3-meter supply cable H05VV-F.3G4mm² in white colour.
Supply cable terminated IEC60309 plug blue 1-phase (32A/230V).
Maximum current 32A (7360 W).
Three AC ammeters with 3 digits LED display, one for each block.

Measurement range 0,1...16A

Measurement accurate ±2,5%.
Built-in web server monitoring function of the current load of individual circuit blocks.
Environmental conditions monitoring, e.g. temperature, humidity, flooding, etc. (option)
Web interface: Ethernet RJ45 (Ethernet 10/100BaseT)
Protocols: TCP/IP, HTTP, HTTPS, SSL, SNMP v1/v2c, SMTP, Syslog, DHCP.
Protection level IP20.
Declaration of Conformity CE.